

# Tyres for Pantera 4504

Dimensions	Pantera	Pantera-W	Pantera-H	Pantera-HW	Load index	Outer diameter in mm
300/95 R52	X	X	X	X	156 D	1890
320/90 R54	X	X	X	X	156 B	1948
340/85 R48	X	X			151 D	1805
380/90 R46	X	X	X	X	168 D	1842
380/90 R46	X	X	X	X	173 D	1842
380/90 R50	X	X	X	X	170 D	1956
380/90 R50	X	X	X	X	175 D	1947
420/80 R46	X				159 D	1840
480/80 R42	X	X			156 B	1840
480/80 R46	X	X	X	X	158 B	1945
480/80 R46	X	X	X	X	177 D	1943
520/85 R42	X	X	X	X	165 D	1956
520/85 R42	X	X	X	X	162 B	1951
520/85 R42	X	X	X	X	162 B	1951
620/70 R38	X				170 B	1864
650/65 R38	X				157 D	1811
710/60 R38	X				160 D	1814

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.

# Tyres for Pantera 7004

Dimensions	Pantera	Pantera-W	Load index	Outer diameter in mm
380/90 R54	X	X	171 D	2054
380/90 R54	X	X	176 D	2050
420/95 R50	X	X	177 D	2052
480/80 R50	X	X	166 D	2050
480/80 R50	X	X	179 D	2050
520/85 R46	X	X	170 D	2052
620/70 R42	X		166 D	1935
650/65 R42	X		170 D	1940
650/65 R42	X		165 D	1936

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.



Pantera 7004

# Technical data: Pantera 4504



Model	Pantera 4504	Pantera 4504-W	Pantera 4504-H	Pantera 4504-HW
Nominal volume (l) / Actual volume (l)	4,500 / 4,750			
Fresh water tank (l)	500			
Working width (m)	21 – 48			
Delivery capacity pump (l/min)	520			
Max. suction capacity (l/min)	700			
Fuel tank capacity (l)	290			
DEF tank (l)	20			
Max. working speed (km/h)	20 (30 optional)			
Transport speed (km/h)	up to 50			
Length (m) (Transport position, incl. external wash down kit)	8.60			
Transport width (m)	2.55	2.75	2.55	2.75
Spraying height min./max. (m) with tyre sizes 380/90 R50	0.35 – 2.65 with lift module 0.35 – 3.35		0.35 – 3.15 with lift module 0.35 – 3.85	
Part-width sections min./max. (number)	7 – 13			
No. of sections with individual nozzle switching: Amaswitch or AmaSelect	up to 96			
Unladen weight (kg)	10,100	10,400	11,100	11,400
Max. total weight (kg)	17,200 (depending on tyres)			
Turning circle, all-wheel steer (m)	4.50			
Track width (m) with tyre sizes 380/90 R50 (offset depth + 50 mm)	1.80 – 2.40	2.25 – 3.00	1.80 – 2.40 (down) 2.10 – 2.60 (up)	2.25 – 3.00 (down) 2.45 – 3.20 (up)
Ground clearance (m) with tyre sizes 380/90 R50	1.20	1.15	1.25 / 1.70 in lower / upper working position	1.25 / 1.70 in lower / upper working position
Engine power	max. 160 kW (218 hp)			

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.

# Technical data: Pantera 7004



Model	Pantera 7004	Pantera 7004-W
Nominal volume (l) / Actual volume (l)	6,600 / 7,000	
Fresh water tank (l)	500	
Working width (m)	24 – 48	
Delivery capacity pump (l/min)	610	
Max. suction capacity (l/min)	750	
Fuel tank capacity (l)	290 / 400	
DEF tank (l)	20	
Max. working speed (km/h)	20 (30 optional)	
Transport speed (km/h)	up to 50	
Length (m) (Transport position, incl. external wash down kit)	9.77	
Transport width (m)	2.55	2.75
Spraying height min./max. (m) with tyre sizes 380/90 R50	0.35 – 2.75 with lift module 0.35 – 3.45	
Part-width sections min./max. (number)	7 – 13	
No. of sections with individual nozzle switching: AmaSwitch or AmaSelect	up to 96	
Unladen weight (kg)	approx. 12.000 kg depending on the level of equipment	
Max. total weight (kg)	20,000	
Turning circle, all-wheel steer (m)	4.50	
Track width (m) with tyre sizes 380/90 R50 (offset depth + 50 mm)	2.00 – 2.75	2.25 – 3.00
Ground clearance (m) with tyre sizes 380/90 R50	1.30	
Engine power	max. 225 kW (306 hp)	

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.