Technical data:

D9 mounted seed drill

Model	D9 2500 Special	D9 3000 Special	D9 3000 Super	D9 3500 Super	D9 4000 Super
Working width[2] (m)	2.50	3.00	3.00	3.50	4.00
Power requirement from (kW/hp)	44/60	44/60	44/60	55/75	55/75
WS coulters: number of rows	15/21	18/25	18/25	21/29	24/33
WS coulters: row spacing (cm)	12.0/16.6	12.0/16.6	12.0/16.6	12.0/16.6	12.0/16.6
RoTeC coulters: number of rows	15/17/21	18/21/25	18/21/25	21/25/29	24/29/33
RoTeC coulters: row spacing (cm)	12.0/14.7/16.6	12.0/14.3/16.6	12.0/14.3/16.6	12.0/14.0/16.6	12.0/13.8/16.6
Hopper capacity without extension (l)	360	450	600	720	830
Hopper capacity with extension (l)	–	850	1,000	1,200	1,380
Weight with WS coulters[1] (kg)	630	690	780	918	1,070
Weight with RoTeC coulters[1] (kg)	710	760	850	1,010	1,180

[1] Weight of base machine with mechanical coulter pressure adjustment, Exact harrow, track markers and tramline control
[2] The actual working width can deviate up to a maximum of 3.2 cm, depending on coulter type

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.