Technical data:

Primera DMC large area seed drill

Model		Primera DMC 6000-2C	Primera DMC 9000-2C	Primera DMC 12000-2C	Primera DMC 12001-2C	Primera DMC 6002-2C
Working width (m)		6.00	9.00	12.00	12.00	6.00
Transport width (mm) Optional with transport kit		3,225 3,000	4,725 4,500	4,725 4,500	4,725 4,500	3,220 3,000
Transport height (mm)	– without filling auger	3,800	3,800	3,800	4,000	3,700
	– with filling auger	4,000	4,000	4,000	4,000	–
Total hopper capacity (l)		4,200	4,200	6,000	13,000	5,000
Seed and fertiliser hopper (l)	– with extension 800 l	5,000	5,000	–	–	–
	– with extension 1,200 l	–	–	7,200	–	–
	– with extension 1,600 l	5,800	5,800	–	–	–
	– with extension 2,400 l	–	–	8,400	–	–
Total weight (empty) (kg)		6,400	10,600	15,000	19,000	9,350
Weight (full) (kg)	– without extension	9,800	14,300	20,100	30,000	13,050
	– with extension 800 l	10,400	14,900	–	–	–
	– with extension 1,200 l	–	–	21,000	–	–
	– with extension 1,600 l	11,000	15,500	–	–	—
	– with extension 2,400 l	–	–	21,900	–	
Attachment		trailed	trailed	trailed	trailed	trailed
Number of openers		32/24	48/36	64/48	64/48	32
Number of opener modules		8	12	16	16	8
Spacing between the coulter (mm)		840/1,120	840/1,120	840/1,120	840/1,120	840/1,120
Row spacing (cm)		18.75/25.00	18.75/25.00	18.75/25.00	18.75/25.00	18.75
Spacing of openers in one row (cm)		75	75	75	75	75
Ground clearance at the openers (mm)		500	500	500	500	500
Central depth control for each coulter module		yes	yes	yes	yes	yes
Coulter pressure (constant) (kg/coulter)		52	52	52	52	52
Operational speed (km/h)		10–18	10–18	10–18	10–18	10–18
Tractor power requirement from (kW/hp)	Row spacing (cm) 18.75	133/180	200/270	280/380	320/480	133/180
	Row spacing (cm) 25.00	118/160	185/250	260/350	295/400	–
Recommended tyre size		700/45-22,5 PR	700/45-22,5 PR	800/45-26,5 PR	850/50-30,5 PR	700/50-26.5 750/45-26,5 VF

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.