



KG 3001 rotary cultivator

KX/KG rotary cultivator

Model	Working width (m)	Transport width (m)	Power requirement from (kW/PS)	For tractors up to (kW/PS)	Number of tine carriers	Base weight without roller from (kg)	Base weight with roller KW 580 from (kg)
KX 3001	3.00	3.00	66/90	142/190	10	1,350	1,969
KG 3001 Special	3.00	3.00	66/90	161/220	10	1,340	1,959
KG 3501 Special	3.50	3.50	77/105	161/220	12	1,450	2,029
KG 4001 Special	4.00	4.03	88/120	161/220	14	1,580	2,199
KG 3001 Super	3.00	3.00	66/90	220/300	10	1,360	1,979
KG 3501 Super	3.50	3.50	77/105	220/300	12	1,480	2,059
KG 4001 Super	4.00	4.12	88/120	220/300	14	1,610	2,229
KG 4002-2	4.00	3.00	88/120	265/360	14	2,840	3,610
KG 5002-2	5.00	3.00	110/150	265/360	16	3,120	4,070
KG 6002-2	6.00	3.00	132/180	265/360	20	3,350	4,390

Packer rollers

Model	Cage roller		Tooth packer roller						Trapezium ring roller			Wedge ring roller				Wedge ring roller with Matrix profile		
	SW 520	4.00	2.50	PW 500	3.00	PW 600	3.50	4.00	TRW 500	TRW 600	TRW 828	KW 520*	KW 580	KW 668	KW 529	KW 606	KW 669	
Working width (m)	3.00	4.00	2.50	3.00	4.00	3.00	3.50	4.00	3.00	3.00	4.00	3.00	3.00	3.50	4.00	3.00	3.50	4.00
Diameter (mm)	520		500			600			500	600		520	580			600		
Base weight from (kg)																		
with 12.5 cm row spacing	-	-	-	-	-	-	-	-	534	638	828	339	521	593	668	529	606	669
with 14.6 cm row spacing	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
with 15.0 cm row spacing	280	359	327	385	500	521	598	675	494	592	-	-	481	-	-	500	-	-
with 15.4 cm row spacing	-	-	-	-	-	-	-	-	-	-	759	-	-	-	603	-	-	638

*only for row spacings of 12.5 cm and a working width of 3 m

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.