



Technical data: Groundkeeper/HorseHopper

| Model | Working width (m) | Tractor mounting | | Category | Collection hopper (l) | Empty weight (kg) | Permissible total weight* (kg) | Dimensions L x W x H (m) |
|-----------------------------|-------------------|-------------------------------------------------|------|-------------|-----------------------|-------------------|--------------------------------|--------------------------|
| | | Recommended tractor power requirement (hp) Min. | Max. | | | | | |
| GH 1350 | 1.35 | 30 | 60 | Cat. I N, I | 1,350 | 570 | 910 | 1.80 x 1.75 x 1.48 |
| GH 1500/HH 1500 | 1.50 | 40 | 80 | Cat. I, II | 1,500 | 600 | 970 | 1.80 x 1.90 x 1.48 |
| GH 1800 Super/HH 1800 Super | 1.80 | 60 | 120 | Cat. I, II | 1,800 | 690 | 1,140 | 1.80 x 2.20 x 1.48 |
| GH 2100 Super/HH 2100 Super | 2.10 | 70 | 130 | Cat. I, II | 2,100 | 760 | 1,290 | 1.80 x 2.50 x 1.48 |

With ground level discharge

| | | | | | | | | |
|------------|------|----|----|-------------|-------|-----|-------|--------------------|
| GHL-T 1350 | 1.35 | 30 | 60 | Cat. I N, I | 1400 | 750 | 1,100 | 1.94 x 1.75 x 1.58 |
| GHL-T 1500 | 1.50 | 40 | 80 | Cat. I, II | 1,550 | 780 | 1,160 | 1.94 x 1.90 x 1.58 |

Discharge height approx. 1.80 m

| | | | | | | | | |
|----------|------|----|-----|------------|-------|-------|-------|--------------------|
| GHS 1500 | 1.50 | 50 | 100 | Cat. I, II | 2,500 | 970 | 1,600 | 2.60 x 1.90 x 1.65 |
| GHS 1800 | 1.80 | 60 | 120 | Cat. I, II | 3,000 | 1,000 | 1,750 | 2.60 x 2.20 x 1.65 |
| GHS 2100 | 2.10 | 70 | 130 | Cat. I, II | 3,500 | 1,040 | 1,915 | 2.60 x 2.50 x 1.65 |

Discharge height approx. 2.20 m

| | | | | | | | | |
|----------------|------|----|-----|---|-------|-------|-------|--------------------|
| GHS Drive 1500 | 1.50 | 50 | 100 | – | 2,500 | 1,030 | 1,660 | 3.55 x 1.90 x 1.70 |
| GHS Drive 1800 | 1.80 | 60 | 120 | – | 3,000 | 1,130 | 1,880 | 3.55 x 2.20 x 1.70 |
| GHS Drive 2100 | 2.10 | 70 | 130 | – | 3,500 | 1,240 | 2,100 | 3.55 x 2.50 x 1.70 |

Discharge height approx. 2.30 m

* Value used for testing the lift capacity and permissible total weight of the tractor (mounted implements) and the permissible total weight of the tractor in operation (mounted implements).



Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



AMAZONE S.A. Forbach

B.P. 90106 · 17, rue de la Verrerie · F-57602 Forbach Cedex
 Phone +33 (0)3 87 84 65 70 · Fax +33 (0)3 87 84 65 71
www.amazone.fr · forbach@amazone.fr