

# Technical data:

## Citan trailed seed drill



Model	Citan 12001-C	Citan 15001-C
Working width (m)	12.00	15.00
Transport width (m)	3.00	
Transport height (m)	3.95	3.95
Transport length (m)	9.00	10.50
Operational speed (km/h)	8–16	
Average work rates (ha/h)	10–12	10–15
Power requirement (kW/hp)	from 170/231	from 210/286
Hopper capacity (l)	7,800	7,800
Division of the 3-section pressurised tank	2,400/2,400/3,000	2,400/2,400/3,000
Linkage	Cat. 3, Cat. 4 or Cat. K700 lower link	
Coulter system	RoTeC pro coulter	
Number of rows	72	90
Row spacing (cm)	12.5/16.6	16.6
Weight (kg)	from 9,500	from 10,500
Operator terminal	AmaLog <sup>+</sup> , ISOBUS	

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.

**Superbly compact folding technology – all Citan models offer a transport width of just 3 m and a minimal transport height.**



Citan 12001-C