

Technical data: D9 6000-TC “Combi” seed drill

	D9 6000-TC “Combi”
Working width (m)	6.00
Transport width in work position (m)	7.40
Transport width with end tow transport trailer (m)	2.75
Number of rows	
– RoTeC coulters	36 (16.6 cm) / 48 (12.5 cm)
– RoTeC ⁺ coulters	36 (16.6 cm) / 48 (12.5 cm)
Hopper capacity seed (l)	1,640
Hopper capacity fertiliser (l)	1,160
Filling height (m)	2.05
Total volume (l)	2,800
Basic weight, empty (RoTeC ⁺ coulters, Roller bar, transport trailer) (kg)	4,050
Support load in operational position (kg)	750
Tractor requirement:	
– pulling capacity (HP)	from 80
– pulling eye height (mm)	50 (530/620)
Hydraulics	
– headland lift	1 x double acting
– track markers, coulter pressure	2 x single acting
– Transport trailer (optional)	1 x double acting

Illustrations, content and technical data are not binding! Technical data may deviate according to the level of equipment.
Machine illustrations can vary due to country-specific traffic legislation.

Safety-first in all situations



Road transport with the end tow transport trailer

Thanks to the end tow transport trailer the machine features a transport width of 2.75 m. A permanently fixed lighting kit is available for AMAZONE seed drills which fulfil the demands for transport safety at road traffic.



AMAZONEN-WERKE H. DREYER GmbH & Co. KG
P. O. Box 51 · 49202 Hasbergen-Gaste/Germany
Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193