

Tyrok semi-mounted reversible ploughs

Model	Tyrok 400 (OL)				Tyrok 400 (OL) S			Tyrok 400 (OL) V			Tyrok 400 (OL) VS		
	6	7	8	9	6	7	8	6	7	8	6	7	8
No. of furrows	6	7	8	9	6	7	8	6	7	8	6	7	8
Tractor power up to (kW/hp)	295/400												
Interbody clearance (cm)	100												
Frame height (cm)	80, 85				80			80, 85			80		
Furrow width adjustment	Manual				Manual			Hydraulic			Hydraulic		
Overload protection	Shear bolt				Hydraulic overload protection			Shear bolt			Hydraulic overload protection		
Furrow width per body (cm)	35, 40, 45, 50				35, 40, 45, 50			33 – 55			33 – 55		
Support wheel (dimension)					400/55-22.5			500/45-22.5			500/60-22.5		
Weight of the base machine, from (kg)	3,540	3,788	4,129	4,279	4,160	4,497	4,853	3,630	3,899	4,140	4,245	4,602	4,860



Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.



AMAZONEN-WERKE H. DREYER SE & Co. KG
 P. O. Box 51 · 49202 Hasbergen-Gaste/Germany
 Phone +49 (0)5405 501-0 · Fax +49 (0)5405 501-193