# Technical data:

## Tyrok semi-mounted reversible ploughs

| Model | Tyrok 400 (OL) | | | | Tyrok 400 (OL) S | | | Tyrok 400 (OL) V | | | | Tyrok 400 (OL) VS | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Number of furrows | 6 | 7 | 8 | 9 | 6 | 7 | 8 | 5* | 6 | 7 | 8 | 5* | 6 | 7 | 8 |
| Tractor power up to (kW/hp) | 295/400 | | | | | | | | | | | | | | |
| Interbody clearance (cm) | 100 | | | | | | | | | | | | | | |
| Beam height (cm) | 80, 85 | | | | 80 | | | 80, 85 | | | | 80 | | | |
| Furrow width adjustment | Manual | | | | Manual | | | Hydraulic | | | | Hydraulic | | | |
| Overload protection | Shear bolt | | | | Hydraulic overload protection | | | Shear bolt | | | | Hydraulic overload protection | | | |
| Furrow width per body (cm) | 35, 40, 45, 50 | | | | 35, 40, 45, 50 | | | 33 – 55 | | | | 33 – 55 | | | |
| Support wheel (dimension) | 400/55-22,5 500/45-22,5 500/60-22,5 | | | | | | | | | | | | | | |
| Weight of the base machine, from (kg) | 3,540 | 3,788 | 4,129 | 4,279 | 4,160 | 4,497 | 4,853 | 3,230 | 3,630 | 3,899 | 4,140 | 3,705 | 4,245 | 4,602 | 4,860 |

*Not available as an Onland version

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.