

Mounted reversible ploughs Teres

Model	Teres 300			Teres 300 S			Teres 300 V			Teres 300 VS		
	4	5	6	4	5	6	4	5	6	4	5	6
No. of furrows	4	5	6	4	5	6	4	5	6	4	5	6
Tractor power up to (kW/hp)	4 furrows: 160/220			5 furrows: 190/260			6 furrows: 220/300					
Interbody clearance (cm)	100			100			90 or 100					
Frame height (cm)	80/85			80			80/85			80		
Furrow width adjustment	Mechanical			Mechanical			Hydraulic			Hydraulic		
Overload protection	-			-			Shear bolt			Hydraulic		
Furrow width per body (cm)	35/40/45/50			35/40/45/50			30 - 50 or 33 - 55					
Support wheel (dimension)	10/75-15.3 or 340/55-16 or 10/75-15											
Weight of the base machine (kg)	1,710	1,965	2,144	1,990	2,320	2,465	1,650	1,910	2,120	1,900	2,220	2,490



Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.