

Teres 200 mounted reversible plough

Model	Teres 200 V		Teres 200 VS	
	No. of furrows	4	5	4
Tractor power up to (kW/hp)	147/200			
Interbody clearance (cm)	90/100			
Frame height (cm)	80/85		80	
Furrow width adjustment	Hydraulic			
Overload protection	Shear bolt		Hydraulic	
Furrow width per body (cm)	30 – 50 or 33 – 55			
Support wheel (dimension)	10/75-15, 10/75-15.3, 340/55-16 or 360/45-17.5			
Weight (kg)	1760	2058	2000	2375

Teres 300 mounted reversible plough

Model	Teres 300			Teres 300 S			Teres 300 V			Teres 300 VS		
	No. of furrows	4	5	6	4	5	6	4	5	6	4	5
Tractor power up to (kW/hp)	4 furrows: 160/220			5 furrows: 190/260			6 furrows: 220/300					
Interbody clearance (cm)	100						90 or 100					
Frame height (cm)	80/85			80			80/85			80		
Furrow width adjustment	Mechanical						Hydraulic					
Overload protection	Shear bolt			Hydraulic			Shear bolt			Hydraulic		
Furrow width per body (cm)	35/40/45/50						30 – 50 or 33 – 55					
Support wheel (dimension)	10/75-15, 10/75-15.3, 340/55-16 or 360/45-17.5											
Weight (kg)	1853	2140	2509	2123	2481	2920	1884	2248	2616	2211	2622	3028