

|                                | <b>Cirrus 9004-2C Grand</b>           |
|--------------------------------|---------------------------------------|
| Coulter system                 | TwinTeC plus                          |
| Row spacing (cm)               | 16.6                                  |
| Working width (m)              | 9.00                                  |
| Transport width (m)            | 2.99                                  |
| Transport height (m)           | 3.97                                  |
| Power requirement from (kW/hp) | 300                                   |
| Seed hopper capacity (l)       | 5,750                                 |
| Fill height (m)                | 3.15                                  |
| Hopper opening (m)             | 2.00x1.25x0.70                        |
| Linkage                        | Lower link cross shaft Cat. 3/4N/K700 |
| Base weight from (kg)          | 13,100                                |
| Transport running gear         | integrated                            |
| Number of Matrix tyres         | 18                                    |

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required. The permissible axle loads and total weights of the tractor should be checked. Not all the listed combination options are possible with all tractor manufacturers.

## SL 3000 wheel mark eradicator frame

If required, the tractor track can be loosened with the wheel mark eradicators which are mounted on an intermediate frame between the drill and tractor. The wheel mark eradicators loosen but do not mix. The soil-engaging parts are hydraulically swivelled up when driving on headlands. Combination with a wide variety of implements for seed-bed preparation is also possible, e.g. with a Catros compact disc harrow.

